



US009409609B2

(12) **United States Patent**
Camosy

(10) **Patent No.:** **US 9,409,609 B2**
(45) **Date of Patent:** **Aug. 9, 2016**

(54) **WAKE CONVERGENCE DEVICE FOR A PICK-UP TRUCK**

296/210, 152, 91; 180/903, 116, 127, 89.1;
293/117

See application file for complete search history.

(71) Applicant: **Auto Research Center, LLC,**
Indianapolis, IN (US)

(56) **References Cited**

(72) Inventor: **Michael Camosy,** Indianapolis, IN (US)

U.S. PATENT DOCUMENTS

(73) Assignee: **Auto Research Center, LLC,**
Indianapolis, IN (US)

2,933,344	A	4/1960	Shumaker
3,010,754	A	11/1961	Shumaker
3,276,811	A	10/1966	Schmidt
3,596,975	A	8/1971	Stephen
3,960,402	A	6/1976	Keck
3,999,797	A	12/1976	Kirsch et al.
4,142,755	A	3/1979	Keedy

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(Continued)

(21) Appl. No.: **14/666,533**

FOREIGN PATENT DOCUMENTS

(22) Filed: **Mar. 24, 2015**

DE	102008036888	2/2010
WO	2013188669	12/2013

(65) **Prior Publication Data**

US 2015/0266521 A1 Sep. 24, 2015

OTHER PUBLICATIONS

Aerodynamic Trailer Systems, LLC SmartTail® The Trucking Industry's First Totally Automated Trailer Air Spoiler from www.ats-green.com/smarttail.htm (2pages), Jan. 13, 2014.

(Continued)

Related U.S. Application Data

(63) Continuation-in-part of application No. 61/969,519, filed on Mar. 24, 2014.

Primary Examiner — Glenn Dayoan

Assistant Examiner — Sunsuraye Westbrook

(51) **Int. Cl.**
B62D 27/06 (2006.01)
B62D 35/00 (2006.01)

(74) *Attorney, Agent, or Firm* — Ice Miller LLP

(52) **U.S. Cl.**
CPC **B62D 35/007** (2013.01); **B62D 27/06** (2013.01)

(57) **ABSTRACT**

(58) **Field of Classification Search**
CPC B62D 35/001; B62D 35/00; B62D 35/004; B62D 35/007; B62D 37/02; B62D 35/02; B62D 63/08; B64C 23/06; B64C 2230/04; B64C 2230/06; B64C 23/00; B64C 21/025; B64C 2230/20; B60J 1/2008; B60J 5/108; B60J 5/062; B60J 5/125
USPC 296/180.4, 208, 96.15, 26.07, 37.6,

A wake convergence device for a pick-up truck is provided. The wake convergence device is spaced from the top of a pick-up truck and from the sides of the pick-up truck. The wake convergence device is moveably coupled to an aft end of the cab of the pick-up truck. When the truck is not in motion, the wake convergence device is positioned around the aft end of the pick-up truck. When the truck is in motion, the wake convergence device is moved upward and raised from the cab of the pick-up truck.

20 Claims, 5 Drawing Sheets

